



## 3D-TOP-HAT BEAM SHAPERS

STABLE TOP-HATS FOR REAL INDUSTRIAL PRODUCTION CONDITIONS.



Beam  
Shaper

Also available from our Partners



In laser micro-machining applications like **precision marking, laser lift-off, precision drilling, fine cutting, or surface structuring**, shaping Gaussian laser beams to **smallest Top-Hat** profiles creates significant benefits in quality or speed. **Yet in production their stability is often limited.** Tight process windows and high sensitivity to focus position make robust operation challenging.

**3D-Top-Hat Beam Shapers are designed to extend the usable working range and support more stable top-hat processes under real industrial conditions.**

### INDUSTRIAL CHALLENGE


Top-Hat beams are typically stable only very close to the focus position.

**In industrial environments this leads to:**

- tight alignment tolerances
- frequent re-adjustment
- limited process windows
- reduced yield stability and rejects

**Result:**

Higher scrap rates, longer setup times and increased cost per part.



### OUR APPROACH

3D-Top-Hat Beam Shapers address this challenge by **engineering the depth of field** of the top-hat profile.

Instead of changing the principle of Top-Hat shaping, we focus on making it **more robust for 24/7 production use.**

### BENEFITS

**Up to 5x larger usable process window**

→ less downtime, less rework

**Lower sensitivity to focus shifts and alignment**

→ stable results across shifts and machines

**Consistent energy distribution for smallest spot sizes** → higher process quality and yield

**Designed for industrial laser systems**

→ not only for ideal lab setups

## IS THIS THE RIGHT BEAM SHAPER FOR YOU?


### 3D-Top-Hat Beam Shapers are made for you if:

- Your top-hat is stable in the lab - but not in production
- Your process is sensitive to focus position
- You need reproducible results across shifts and machines
- You work with small spot sizes and tight tolerances

Then it is time for depth-of-field engineered Top-Hat shaping.

## DEPTH-OF-FIELD ENGINEERED TOP-HAT SHAPING

Conventional Top-Hat solutions shape the beam mainly in the focus plane. In production, however, process stability depends on behavior across depth of field. 3D-Top-Hat Beam Shapers are designed to keep the top-hat stable over a defined axial range - extending the usable working range under realistic system conditions.



## PERFORMANCE

- **Usable DOF:** stable top-hat across  $\pm 60\%$   $z_{\text{Rayleigh}}$
- **Flatness:** > 0.9 across usable DOF
- **Plateau uniformity:** < 0.1 across usable DOF
- **Beam shaping efficiency:** > 82 %
- **Side lobes:** < 5 % of  $I_{\text{TopHat-Plateau}}$
- **Reflectivity:** > 99.9 % (Dielectric-HR-coating)

(values refer to aberration-free optical systems,  $M^2 = 1.0$ , System aberrations and beam quality may influence the achieved results)


## FOR INDUSTRIAL CONDITIONS

**3D-Top-Hat Beam Shapers are made for real industrial laser systems.**

- **Input beam:**  $M^2 \leq 1.3$ ,  $TEM_{00}$ , CW to ultrashort pulses down to 300 fs
- **Optical design:** Continuous DOE based on micro-structured mirror (All reflective approach, dielectric HR coating)
- **Made for Power** → See specs on our website
- **Dimensions:**  $\varnothing 25.0\text{ mm} \times 6.35\text{ mm}$

## WHAT YOU GAIN IN PRACTICE

- Larger usable process window compared to conventional Top-Hat solutions
- Lower sensitivity to small focus shifts and alignment tolerances
- More consistent energy distribution in smallest spot applications
- Higher confidence when scaling from pilot to series production




## WHERE STABLE TOP-HATS MATTER

Stable Top-Hat profiles are especially critical in applications that require uniform energy delivery, small spot sizes and challenging tight process windows.

**3D-Top-Hat Beam Shapers are typically used in the following scenarios:**

Application	Usecase	Key Industries
<b>High-Quality (Black) Marking</b>	Deep, uniform contrast; no hot spots → premium quality	Consumer electronics, Automotive
<b>Laser Lift-Off (LLO)</b>	Controlled delamination; homogeneous energy delivery	Displays (OLED, $\mu$ LED, flexible)
<b>Precision Drilling</b>	Minimal taper; minimal heat-affected zone	PCB, Semiconductor packaging, TGV, Glass
<b>Surface Microstructuring</b>	Repeatable textures; functionalized surfaces	Medical devices, Automotive, PV
<b>Fine Cutting</b>	Smooth edges; minimal recast/burr	Wafer Dicing, Medical Tech, Displays

## INTEGRATION OPTIONS





## TOP-HAT PARAMETERS

Output Shape	Round Top-Hat (Gaussian to Top-Hat Conversion)			
Shaped Beam Diameter (x Diffraction Limit of Unshaped Beam)	For $M^2=1.0$ 1.8 x DL ( $1/e^2$ )	$M^2=1.1$ 1.7 x DL ( $1/e^2$ )	$M^2=1.2$ 1.6 x DL ( $1/e^2$ )	$M^2=1.3$ 1.5 x DL ( $1/e^2$ )
Efficiency	$\geq 85\%$ (Encircled energy ( $1/e^4$ )/ Total Energy)			
Top-Hat Quality	Plateau Uniformity $\leq 0.1$ & Flatness $\geq 0.9$ (ISO 13694)			
Strongest Side Order	Intensity $\leq 5\%$ (Relative to Top-Hat Plateau)			
Stable z-Region (x Rayleigh Length of Unshaped Beam)	For $M^2=1.0$ 1.2 x $Z_{RL}$	$M^2=1.1$ 1.0 x $Z_{RL}$	$M^2=1.2$ 0.6 x $Z_{RL}$	$M^2=1.3$ 0.3 x $Z_{RL}$

## INPUT BEAM REQUIREMENTS

Input Beam	Gaussian, TEM <sub>00</sub> , $M^2 \leq 1.3$ , CW to ultrashort pulses down to 300 fs
Input Beam Diameter ( $1/e^2$ )	Available for 2.5mm   5.0mm   8.0mm
Wavelengths	Available for 1030-1064nm   515-532nm   343-355 nm
System Requirements	Clear aperture $\geq 2x$ beam diameter ( $1/e^2$ ), Integrate into collimated beam with a focusing lens. Lateral alignment required
Angle of Incidence	45.0°

## ELEMENT PARAMETERS

Element	Micro-structured Mirror (Continuous Reflective DOE)
Coating	$>99.9\%$ at 45.0° Dielectric HR Coating on flat fused silica substrate
Dimensions	Diameter: $\varnothing 25.0\text{mm}$ (+0.0mm -0.1mm) Thickness: 6.35mm (+/- 0.10mm)

Performance values are specified for a TEM<sub>00</sub> Gaussian input with diffraction-limited wavefront quality at the DOE plane ( $\lambda/10$  RMS or better) and sufficient clear aperture.

### FIND YOUR CONFIGURATION AND GET STARTED

Use our online tool to check performance for your laser parameters



<https://midel-photonics.de/3d-top-hat-tool>

## ABOUT MIDEL PHOTONICS

Founded in 2022, Midel Photonics GmbH is revolutionizing the photonic industry through innovative beam shaping. Our award-winning high-tech company sets new standards for precision and efficiency. With over 100 individually developed optical solutions, our team of experienced specialists provides customers with decisive competitive advantages.

**Midel Photonics GmbH**  
**Maarstr. 96, 53227 Bonn, Germany**  
**[www.midel-photonics.de](http://www.midel-photonics.de)**  
**Phone: +49 228 28679710**

